

冷暖變頻一拖多機式系統

INVERTER MULTI-SPLIT TYPE SYSTEMS (COOLING/HEATING)

無論製冷或供暖，此一拖多機式系統均便捷、經濟及節省空間。

This Multi-split type System is Convenient, Economical and Space Saving in the Cooling or Heating Mode.

連接2台室內機
2-unit ALL DC **AOHG14LAC2**

連接3台室內機
3-unit ALL DC **AOHG18LAT3** ALL DC **AOHG24LAT3**

連接4台室內機
4-unit ALL DC **AOWG30LAT4**



連接2台室內機 2-unit



連接3台室內機 3-unit



連接4台室內機 4-unit

	Outdoor Unit	2-unit		3-unit	
		AOHG14LAC2	AOHG18LAT3	AOHG18LAT3	AOHG24LAT3
		Cooling	4.0	5.4	5.4
Heating	4.4	6.8	6.8	8.0	
Indoor Unit		kW Class			
掛牆式 WALL MOUNTED	ASHG07/09/12/14LM	2.0	●	●	●
		2.5	●	●	●
		3.5	●	●	●
		4.0	—	●	●
	ASHG18/24LF	5.0	—	—	●
		7.0	—	—	—
小型藏天花式 CASSETTE (COMPACT)	AUHG09/12/18LV	2.5	●	●	●
		3.5	●	●	●
		5.0	—	—	●
薄型氣管式 SLIM DUCT	ARHG09LLTA ARHG12/18LLTB	2.5	●	●	●
		3.5	●	●	●
		5.0	—	—	●

便於安裝

Flexible installation

AOHG14LAC2

雪種喉最長達30米而無須添加雪種。

AOHG18LAT3 / 24LAT3

最長達50米。30米內無須添加雪種。

AOWG30LAT4 最長達70米。50米內無須添加雪種。

此機種的室外機適合安裝於很多不同類型的房屋。


AOHG36LBLA5, AOHG45LBLA6 最長達80米。50米內無須添加雪種。

此機種的室外機適合安裝於很多不同類型的房屋。

The outdoor unit can be installed in a wide range of properties by the long piping of 30m (gas chargeless) for AOHG14LAC2, 50m (gas chargeless up to 30m) for AOHG18LAT3 / 24LAT3, 70m (gas chargeless up to 50m) for AOWG30LAT4, 80m (gas chargeless up to 50m) for AOHG36LBLA5 AOHG45LBLA6


可安裝最長管道距離 Max.piping length (Each unit)

20m (AOHG14LAC2)
25m (AOHG18LAT3 / 24LAT3,
AOWG30LAT4, AOHG36LBLA5,
AOHG45LBLA6)



可安裝最高距離 Max.height

15m (AOHG14LAC2,
AOHG18LAT3 / 24LAT3,
AOWG30LAT4, AOHG36LBLA5,
AOHG45LBLA6)



總管道長度 Total Piping Length:

30m (AOHG14LAC2)
50m (AOHG18LAT3 / 24LAT3)
70m (AOWG30LAT4)
80m (AOHG36LBLA5, AOHG45LBLA6)

冷暖變頻一拖多機式系統

INVERTER MULTI-SPLIT TYPE SYSTEMS (COOLING/HEATING)

可按喜好選擇適合您房間環境的任何機款。

Select any type of air conditioners you like to suit the atmosphere of your room.



規格 SPECIFICATIONS

掛牆式 WALL MOUNTED TYPE

型號 Model No.	室內機 Indoor Unit		ASHG07LMCA	ASHG09LMCA	ASHG12LMCA	ASHG14LMCA	
能力 Capacity	製冷 Cooling	千瓦(英制)階級 kW(BTU/h) class	2.1 (7,200)	2.5 (8,500)	3.5 (12,000)	4.0 (13,700)	
	供暖 Heating		2.7 (9,200)	3.3 (11,300)	4.0 (13,700)	4.8 (16,400)	
電壓/相-頻率 Power Source	伏特/〇-赫茲 V/〇/Hz		230/1/50	230/1/50	230/1/50	230/1/50	
噪音 Noise	製冷 Cooling	高/中/低/靜 H/M/L/Q	分貝 dB(A)	36/32/29/21	37/33/29/21	40/36/30/21	42/38/33/25
氣流(高能力) Air flow (High)	立方米/時 m³/h		560	600	660	730	
外形尺寸 高×寬×深 Dimensions H×W×D	毫米 mm		268×840×203	268×840×203	268×840×203	268×840×203	
淨重 Net Weight	公斤(磅) kg(lbs)		8.5(19)	8.5(19)	8.5(19)	8.5(19)	

掛牆式 WALL MOUNTED TYPE

型號 Model No.	室內機 Indoor Unit		ASHG18LFCA	ASHG24LFCC	
能力 Capacity	製冷 Cooling	千瓦(英制)階級 kW(BTU/h) class	5.0 (17,100)	6.8 (23,200)	
	供暖 Heating		6.0 (20,500)	8.2 (28,200)	
電壓/相-頻率 Power Source	伏特/〇-赫茲 V/〇/Hz		230/1/50	230/1/50	
噪音 Noise	製冷 Cooling	高/中/低/靜 H/M/L/Q	分貝 dB(A)	43/37/33/26	49/42/37/33
氣流(高能力) Air flow (High)	立方米/時 m³/h		900	1,120	
外形尺寸 高×寬×深 Dimensions H×W×D	毫米 mm		320×998×238	320×998×238	
淨重 Net Weight	公斤(磅) kg(lbs)		14(30.8)	14(30.8)	

小型藏天花式 CASSETTE (COMPACT) TYPE

型號 Model No.	室內機 Indoor Unit		AUHG09LVLA	AUHG12LVLB	AUHG18LVLB	
能力 Capacity	製冷 Cooling	千瓦(英制)階級 kW(BTU/h) class	2.5 (8,500)	3.5 (12,000)	5.0 (17,100)	
	供暖 Heating		3.3 (11,300)	4.0 (13,700)	6.0 (20,500)	
電壓/相-頻率 Power Source	伏特/〇-赫茲 V/〇/Hz		230/1/50	230/1/50	230/1/50	
噪音 Noise	製冷 Cooling	高/中/低/靜 H/M/L/Q	分貝 dB(A)	33/31/29/27	37/33/31/28	42/37/33/29
氣流(高能力) Air flow (High)	立方米/時 m³/h		540	610	750	
外形尺寸 高×寬×深 Dimensions H×W×D	毫米 mm		245×570×570	245×570×570	245×570×570	
淨重 Net Weight	公斤(磅) kg(lbs)		15(33.1)	15(33.1)	15(33.1)	
風葉 Grille			UTG-UFGD-W			
Grille size	毫米 mm		49×700×700			

規格 SPECIFICATIONS

薄型氣管式 SLIM DUCT TYPE

型號 Model No.	室內機 Indoor Unit		ARHG09LLTA	ARHG12LLTB	ARHG18LLTB	
能力 Capacity	製冷 Cooling	千瓦(英卡/時)階級 kW(BTU/h)class	2.5 (8,500)	3.5 (12,000)	5.0 (17,100)	
	供暖 Heating		3.3 (11,300)	4.0 (13,700)	6.0 (20,500)	
電壓/相-頻率 Power Source	伏特/0-赫茲 V/0/Hz		230/1/50	230/1/50	230/1/50	
噪音 Noise	製冷 Cooling	高/中/低/靜 H/M/L/Q	分貝 dB(A)	28/27/26/25	29/28/27/26	32/31/30/29
				氣流(高能力) Air flow (High)	立方米/時 m³/h	600
外形尺寸 高×寬×深 Dimensions H×W×D	毫米 mm		198×700×620	198×700×620	198×900×620	
淨重 Net Weight	公斤(磅) kg(lbs)		19(41.8)	19(41.8)	23(51)	

2台室內機 3台室內機 4台室內機 5台室內機 6台室內機 2-UNIT, 3-UNIT, 4-UNIT, 5-UNIT, 6-UNIT

型號 Model No.	室外機 Outdoor Unit		AOHG14LAC2	AOHG18LAT3	AOHG24LAT3	AOWG30LAT4	AOHG36LBA5	AOHG45LBA6
能力 Capacity	製冷 Cooling	千瓦(英卡/時) kW (BTU/h)	4.0 (13,700)	5.4 (18,400)	6.8 (23,200)	8.0 (27,300)	10.0 (34,100)	12.5 (42,700)
	供暖 Heating		4.4 (15,000)	6.8 (23,200)	8.0 (27,300)	9.6 (32,800)	12.0 (41,000)	13.5 (46,100)
電壓/相-頻率 Power Source	伏特/0-赫茲 V/0/Hz		230/1/50	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
運轉電流 Running Current	製冷 Cooling	安培 A	5.10	5.90	8.50	9.70	10.60	15.70
	供暖 Heating		4.90	7.10	8.80	10.50	12.30	14.90
噪音 Noise	製冷 Cooling	分貝 dB(A)	47	46	48	50	53	53
外形尺寸 高×寬×深 Dimensions H×W×D	毫米 mm		540×790×290	700×900×330	700×900×330	830×900×330	998×970×370	998×970×370
淨重 Net Weight	公斤(磅) kg(lbs)		37(82)	55(121)	55(121)	68(150)	94(207)	94(207)
管道接口 Piping Connections	小(液體) Small Ø (Liquid)	毫米 mm	6.35×2	6.35×3	6.35×3	6.35×4 *(6.35×3, 9.52)	6.35×5 *(9.52×3, 12.70×2)	6.35×6 *(9.52×2, 15.88×2, 12.70)
	大(氣體) Large Ø (Gas)		9.52×2	9.52×2, 12.7 *(9.52×3)	9.52×2, 12.7 *(9.52×3)	9.52×2, 12.7×2 *(9.52×3, 12.7) *(9.52×2, 12.7, 15.88)	9.52×3 + 12.70×2, *(9.52×2, 15.88×2, 12.70)	9.52×4 + 12.70×2, *(9.52×2, 15.88×2, 12.70)
最大管道長度距離 Max Pipe Length	總合長 Total	米 m	30	50	50	70	80	80
	單獨長 Each		20	25	25	25	25	25
最大高度距離 Max Height Difference	室外機和每個室內機之間 Between outdoor unit and each indoor unit	米 m	15	15	15	15	15	15
	室內機之間 Between indoor units		10	10	10	10	10	10
操作範圍 Operation Range	製冷 Cooling	攝氏(度) °C	10~46	-10~46	-10~46	0~46	-10~46	-10~46
	供暖 Heating		-15~24	-15~24	-15~24	-10~24	-15~24	-15~24
冷媒 Refrigerant			R410A					

* 通過轉換器與接口的閥門相連接 *Connect to connection valve by the adapter

2台室內機 2-unit Multi-split :

AOHG14LAC2 : 可以連接總制冷量為 4.0kW-6.0kW 室內機組
AOHG14LAC2: Total capacity of indoor units 4.0 kW - 6.0 kW can be connected

3台室內機 3-unit Multi-split :

AOHG18LAT3 : 可以連接總制冷量為 4.0kW-8.5kW 室內機組
AOHG18LAT3: Total capacity of indoor units 4.0 kW - 8.5 kW can be connected
AOHG24LAT3 : 可以連接總制冷量為 4.0kW-10.5kW 室內機組
AOHG24LAT3: Total capacity of indoor units 4.0 kW - 10.5 kW can be connected

4台室內機 4-unit Multi-split :

AOWG30LAT4 : 可以連接總制冷量為 7.5kW-14.0kW 室內機組
AOWG30LAT4: Total capacity of indoor units 7.5 kW - 14.0 kW can be connected

5台室內機 5-unit Multi-split :

AOHG36LBA5 : 連接的室內機總容量必須在 7.5 kW-15.5kW 之間
AOHG36LBA5: Total capacity of indoor units connected must be between 7.5 kW and 15.5 kW

6台室內機 6-unit Multi-split :

AOHG45LBA6 : 連接的室內機總容量必須在 9.5 kW-18.0kW 之間
AOHG45LBA6: Total capacity of indoor units connected must be between 9.5 kW and 18.0 kW